


# PXR-Q1MWS QR Code Reader



## Features

- Conforms to ISO 14443A, supporting MIFARE card.
- Unique ID or Block read format supported and programmable key value.
- Case sensor detection function to enhance the system security.
- Provides Wiegand & RS-485 communication interfaces for more flexible applications.
- Support scanning static QR code (smart phone or paper printing) and dynamic QR code (with APP).
- Supports to scan a QR Code from your smart phone or paper
- Support QR Code scanning function to replace RFID cards sensing
- Case sensor detection function to enhance the system security.
- Wide range of operating temperature to meet the requirements of tropical or frigid zone climate environment.
- Watchdog function secures system free from halting.

## Ordering Information

Please scan QR Code below to download mCard App



For Android




For iOS

### Package Content:

- PXR-Q1 x 1
- Quick Start Guide x 1
- Accessory Pack x 1

### Model No. Identification

#### P X R - Q 1 M W S



### Color

●  
Black  
(BL)

## Specifications

Model No.	<b>PXR-Q1MWS</b>	
Read Format	Mifare (13.56 MHz)	
Read Range	3 cm above	
QR Code Scan	Auto scan : Get close to scan automatically Supports to scan a QR Code from your smart phone or paper Scan Distance : 5 CM above	
Comm. Interface	RS-485 X 1 、 Wiegand × 1	
ID Setting	6 DIP Switch	
Input Port	Case Sensor x 1	
LED Indicator	Green / Red Bi-color LED x 1 (Status / Power)	
Beep Tone	Buzzer	
Power Input	DC 12V	
Current Consumption	300mA (max)	
Operating Temp.	-20°C~ 70°C / -4°F~ 158°F	
Relative Humidity	20% ~ 80%(Non-condensing)	
Dimensions (mm)	Faceplate : 86(L) x 86(W) x 14(H)    Backside box : 65(L) x 58(W) x 24(H)	